

AMENDMENTS IN THE CLAIMS

RECEIVED  
CENTRAL FAX CENTER  
FEB 11 2008

1 1. (Previously presented) A method comprising the steps of:  
2 sending one or more upstream signals as pulse code modulated data without packet  
3 headers using an upstream cable protocol, wherein at least one of the one or more upstream  
4 signals is a video signal;  
5 sending one or more downstream signals as pulse code modulated data without packet  
6 headers using a downstream cable protocol; and  
7 enclosing the one or more downstream signals as the pulse code modulated data without  
8 application-level packet headers in a Motion Pictures Experts Group (MPEG) transport.

1 2. (Previously presented) The method of claim 1, wherein the upstream protocol is Data-  
2 Over-Cable System Interface Specification (DOCSIS).

1 3. (Original) The method of claim 1, wherein the step of sending one or more upstream  
2 signals comprises mapping one or more pulse code modulated samples of the one or more  
3 signals taken at a sampling interval to an allocation of mini-slots in the upstream protocol.

1 4. (Original) The method of claim 3, wherein the sampling interval is 125 microseconds  
2 and the mini-slots occur at 6.25 microsecond intervals.

1 5. (Original) The method of claim 1, further comprising the step of multiplexing two or  
2 more signals in one mini-slot in the upstream protocol.

1           6. (Previously presented) The method of claim 1, wherein the downstream protocol is  
2   Data-Over-Cable System Interface Specification (DOCSIS).

1           7. (Original) The method of claim 1, wherein the step of sending one or more  
2   downstream signals comprises mapping one or more pulse code modulated samples of the one or  
3   more signals taken at a sampling interval to a Motion Pictures Experts Group (MPEG) transport  
4   layer.

1           8. (Original) The method of claim 1, wherein the step of sending one or more  
2   downstream signals comprises multiplexing multiple signals within a single Motion Pictures  
3   Experts Group (MPEG) packet identifier.

1           9. (Original) The method of claim 1, wherein the method is performed in a cable system  
2   having a media terminal adapter (MTA), such that subscriber signalling functionality is reduced  
3   in the MTA.

1           10. (Original) The method of claim 1, wherein the method reduces throughput delay and  
2   jitter for signals, thereby improving signal quality over existing transport methods.

1           11. (Currently amended) The method of claim 1, wherein [[the]] at least one of the one or  
2   more upstream signals and the one or more downstream signals is a voice signal.

1           12. (Original) The method of claim 1, wherein at least one of the one or more upstream  
2   signals and the one or more downstream signals is a video signal.

1 13. – 20. (Canceled)

1 21. (Previously presented) A method comprising the steps of:

2 providing one or more signals at a sampling interval, yielding pulse code modulated  
3 (PCM) data;

4 transporting downstream signals as the PCM data without packet headers over a cable  
5 media using a downstream cable protocol, wherein at least one of the downstream signals is a  
6 video signal; and

7 enclosing the downstream signals as the pulse code modulated data without application-  
8 level packet headers in a Motion Pictures Experts Group (MPEG) transport.

1 22. (Previously presented) The method of claim 21, wherein the downstream protocol is  
2 Data-Over-Cable System Interface Specification (DOCSIS).

1 23. (Original) The method of claim 21, wherein the step of providing the one or more  
2 signals comprises mapping each byte of pulse code modulated data to a Motion Pictures Experts  
3 Group (MPEG) transport layer.

1 24. (Original) The method of claim 21, wherein the step of providing the one or more  
2 signals comprises multiplexing multiple signals within a single Motion Pictures Experts Group  
3 (MPEG) packet identifier.

1 25. (Original) The method of claim 21, wherein the method reduces throughput delay and  
2 jitter for signals, thereby improving signal quality over existing transport methods.

1           26. (Original) The method of claim 21, wherein at least one of the one or more signals is  
2   a voice signal.

1           27. (Original) The method of claim 21, wherein at least one of the one or more signals is  
2   a video signal.

1           28. (Previously presented) An apparatus comprising:  
2           a sampler, arranged and constructed to sample one or more signals at a sampling interval,  
3   yielding pulse code modulated (PCM) data; and  
4           a transport device, arranged and constructed to transport the PCM data without packet  
5   headers over a cable media using an upstream cable protocol;  
6           wherein the transport device transports downstream signals enclosed as the pulse code  
7   modulated data without application-level packet headers in a Motion Pictures Experts Group  
8   (MPEG) transport, and wherein at least one of the downstream signals is a video signal.

1           29. (Previously presented) The apparatus of claim 28, wherein the upstream protocol is  
2   Data-Over-Cable System Interface Specification (DOCSIS).

1           30. (Original) The apparatus of claim 28, wherein the step of sampling the one or more  
2   signals comprises mapping each byte of pulse code modulated data to one of a plurality of mini-  
3   slots in the upstream protocol.

1           31. (Original) The apparatus of claim 30, wherein the sampling interval is 125  
2   microseconds and each of the plurality of mini-slots occurs at 6.25 microsecond intervals.

1 32. (Original) The apparatus of claim 28, further comprising a multiplexor for  
2 multiplexing two or more signals in one mini-slot in the upstream protocol.

1 33. (Original) The apparatus of claim 28, wherein the apparatus reduces throughput delay  
2 and jitter for signals, thereby improving signal quality over existing transport methods.

1 34. (Original) The apparatus of claim 28, wherein at least one of the one or more signals  
2 is a voice signal.

1 35. (Previously presented) The apparatus of claim 28, wherein at least one of the one or  
2 more signals is the video signal.

1 36. (Original) The apparatus of claim 28, wherein the apparatus is part of a media  
2 terminal adapter.

1 37. (Canceled)

1 38. (Currently amended) The method of claim 1, wherein the step of sending one or more  
2 upstream signals further comprises [[the]] a step of sending the one or more upstream signals as  
3 pulse code modulated data in a form that allows transfer to Public Switched Telephone Network  
4 (PSTN) without transcoding the pulse code modulated data of the one or more upstream signals.

1 39. (New) The method of claim 1, wherein the upstream cable protocol utilizes  
2 Frequency Division Multiple Access burst modulation format.

1

LUC-300 / Dombkowski 7-4

- 1 40. (New) The method of claim 1, wherein the upstream cable protocol utilizes Time
- 2 Division Multiple Access burst modulation format.